

**Description**

Fastener Length: 1/2", Thread: 3/8-24, Head Width: 5/16", Thread Length: 1/2", NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1351N68                                |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5305-01-389-7198                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1351N6-8 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.500 Inches Maximum   |
| <b>Fastener Length:</b>                               | 0.470 Inches Minimum And 0.500 Inches Maximum  |
| <b>Head Style:</b>                                    | Flat Chamfer   |
| <b>Head Diameter:</b>                                 | 0.550 Inches Minimum And 0.562 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.368 Inches Minimum And 0.375 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches   |
| <b>Width Across Flats:</b>                            | 0.3125 Inches Minimum And 0.3160 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall                                      |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unrf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1351 Professional/industrial Association Standard   |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N6-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.