

Description

Fastener Length: 1-63/64", Thread: 15/32-20, Head Width: 3/8", Thread Length: 1-3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351N732
Minimum Qty (MOQ):	1
NSN:	5305-01-378-9268
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS1351N7-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.375 Inches Minimum
Fastener Length:	1.940 Inches Minimum And 2.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.642 Inches Minimum And 0.656 Inches Maximum
Head Height:	0.430 Inches Minimum And 0.437 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.483 Inches
Width Across Flats:	0.375 Inches Minimum And 0.379 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/Industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N7-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.