

Description

Fastener Length: 1-3/4", Thread: 1/2-20, Head Width: 3/8", Thread Length: 1-1/2", NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351N828
Minimum Qty (MOQ):	1
NSN:	5305-01-378-9267
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



\* See page 2 for technical characteristics

## P/N NAS1351N8-28 Specifications

<b>Thread Class:</b>	Aal
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.500 Inches Minimum
<b>Fastener Length:</b>	1.690 Inches Minimum And 1.750 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.735 Inches Minimum And 0.750 Inches Maximum
<b>Head Height:</b>	0.492 Inches Minimum And 0.500 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Width Across Flats:</b>	0.375 Inches Minimum And 0.379 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unrf
<b>Specification/standard Data:</b>	80205-nas1531 Professional/industrial Association Standard

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N8-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.