

P/N NAS1352-02-10P

Description

Fastener Length: 5/8", Thread: 2-56, Head Width: 5/64", Thread Length: 5/8", NAS1352 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS13520210P

Minimum Qty (MOQ):

NSN: 5305-01-010-9927

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N NAS1352-02-10P Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.625 Inches Minimum |
| Fastener Length: | 0.595 Inches Minimum And 0.625 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.134 Inches Minimum And 0.140 Inches Maximum |
| Head Height: | 0.083 Inches Minimum And 0.086 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.086 Inches |
| Width Across Flats: | 0.078 Inches Minimum And 0.079 Inches Maximum |
| Thread Quantity Per Inch: | 56 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 155000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-02-10P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.