

Description

Fastener Length: 47/64", Thread: 2-56, Head Width: 5/64", Thread Length: 45/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS13520212P |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-480-3978 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1352-02-12P Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.698 Inches Minimum And 0.766 Inches Maximum |
| Fastener Length: | 0.734 Inches Minimum And 0.766 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.134 Inches Minimum And 0.140 Inches Maximum |
| Head Height: | 0.083 Inches Minimum And 0.086 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.086 Inches |
| Width Across Flats: | 0.078 Inches Minimum And 0.079 Inches Maximum |
| Thread Quantity Per Inch: | 56 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 155000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/Industrial Association Standard |

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-02-12P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.