

## P/N NAS1352-03-4P

## **Description**

Fastener Length: 11/32", Thread: 3-48, Head Width: 1/16", Thread Length: 1/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1352034P

Minimum Qty (MOQ): 5

NSN: 5305-01-521-5128

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093483, Bolts, nuts Or Screws, noi Iron Or









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352-03-4P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.349 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.154 Inches Minimum And 0.161 Inches Maximum
Head Height:	0.095 Inches Minimum And 0.099 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.099 Inches
Width Across Flats:	0.078 Inches Minimum
Thread Quantity Per Inch:	48
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-03-4P">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-03-4P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.