

Description

Fastener Length: 11/32", Thread: 3-48, Head Width: 1/16", Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352034P
Minimum Qty (MOQ):	5
NSN:	5305-01-521-5128
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093483, Bolts,nuts Or Screws,noi Iron Or



P/N NAS1352-03-4P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.349 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.154 Inches Minimum And 0.161 Inches Maximum
Head Height:	0.095 Inches Minimum And 0.099 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.099 Inches
Width Across Flats:	0.078 Inches Minimum
Thread Quantity Per Inch:	48
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-03-4P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.