

Description

Fastener Length: 3/16", Thread: 4-40, Head Width: 3/32", Thread Length: 3/16", NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352043
Minimum Qty (MOQ):	25
NSN:	5305-01-266-8562
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1352-04-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.096 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.158 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.0937 Inches Minimum And 0.0942 Inches Maximum
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-04-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.