

P/N NAS1352-04-5

Description

Fastener Length: 27/64", Thread: 4-40, Head Width: 3/32", Thread Length: 5/16", NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352045

Minimum Qty (MOQ): 20

NSN: 5305-01-478-8432

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N NAS1352-04-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.3125 Inches Maximum
Fastener Length:	0.4205 Inches Minimum And 0.4245 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.094 Inches Minimum
Thread Quantity Per Inch:	40
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Thread Series Designator:	Unjc

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-04-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.