

**Description**

Fastener Length: 1/4", Hole Diameter: ", Thread: 4-40, Head Width: 3/32", Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS135204H4                               |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-00-052-5694                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1352-04H4 Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Thread Class:</b>                | 3a  |
| <b>Thread Direction:</b>            | Right-hand  |
| <b>Thread Length:</b>               | 0.250 Inches Minimum  |
| <b>Fastener Length:</b>             | 0.250 Inches Nominal  |
| <b>Head Style:</b>                  | Flat Chamfer  |
| <b>Head Diameter:</b>               | 0.176 Inches Minimum And 0.183 Inches Maximum                       |
| <b>Head Height:</b>                 | 0.108 Inches Minimum And 0.112 Inches Maximum                       |
| <b>Hole Diameter:</b>               | 0.031 Inches Nominal  |
| <b>Internal Drive Style:</b>        | Hexagon   |
| <b>Nominal Thread Diameter:</b>     | 0.112 Inches  |
| <b>Width Across Flats:</b>          | 0.093 Inches Minimum And 0.095 Inches Maximum                       |
| <b>Hole Quantity:</b>               | 2   |
| <b>Hole Type:</b>                   | Drilled   |
| <b>Thread Quantity Per Inch:</b>    | 40  |
| <b>Minimum Tensile Strength:</b>    | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>             | 36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>      | 130000 Pounds Per Square Inch                                       |
| <b>Hole Configuration Style:</b>    | Round Internal Hexagon  |
| <b>Material:</b>                    | Steel Overall   |
| <b>Thread Series Designator:</b>    | Unc   |
| <b>Specification/standard Data:</b> | 80205-nas1352 Professional/industrial Association Standard          |

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-04H4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.