

## P/N NAS1352-04H8

## **Description**

Fastener Length: 33/64", Hole Diameter: 1/32", Thread: 4-40, Head Width: 3/32", Thread Length: 33/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

National Motor Freight:

SKU / Model:	NAS135204H8
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-165-7962
Schedule B:	7318.15.6080
ECCN:	EAR99

093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352-04H8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.434 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	0.484 Inches Minimum And 0.516 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Hole Diameter:	0.036 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Hole Configuration Style:	Round
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

### **How to Order**

Order this socket head screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-04H8">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-04H8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.