

P/N NAS1352-04H8P

Description

NAS1352-04H8P Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information


SKU / Model: NAS135204H8P

Minimum Qty (MOQ): 20

NSN: 5305-01-020-9558

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1352-04H8P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.420 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Hole Diameter:	0.036 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Hole Configuration Style:	Round Longitudinal Hole
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-04H8P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.