

**Description**

Fastener Length: 25/64", Thread: 4-40, Head Width: 3/32", Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS135204LL6P                             |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5305-00-234-7814                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1352-04LL6P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.309 Inches Minimum And 0.391 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 0.359 Inches Minimum And 0.391 Inches Maximum                       |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.176 Inches Minimum And 0.183 Inches Maximum                       |
| <b>Head Height:</b>                                   | 0.108 Inches Minimum And 0.112 Inches Maximum                       |
| <b>Locking Feature:</b>                               | Strip Threads   |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.112 Inches  |
| <b>Width Across Flats:</b>                            | 0.094 Inches Minimum And 0.095 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>                      | 40  |
| <b>Minimum Tensile Strength:</b>                      | 180000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>                        | 155000 Pounds Per Square Inch                                       |
| <b>Material:</b>                                      | Plastic Polyamide Locking Feature                                   |
| <b>Material:</b>                                      | Steel Fastener  |
| <b>Surface Treatment:</b>                             | Cadmium Fastener And Chromate Fastener                              |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Fastener |
| <b>Thread Series Designator:</b>                      | Unjc  |
| <b>Specification/standard Data:</b>                   | 80205-nas1352 Professional/industrial Association Standard          |

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-04LL6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.