

Description

Fastener Length: 3/4", Thread: 6-32, Head Width: 7/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS13520613P
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-414-0798
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1352-06-13P Specifications

Thread Class:	3a
Fastener Length:	0.812 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Overall
Material Document And Classification:	Fed 66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-06-13P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.