



★ FASTENERS

Military-Fasteners.com

P/N NAS1352-06H4P

## Description

drilled head, hex drive, cadmium

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS135206H4P                              |
| Minimum Qty (MOQ):      | 20  |
| NSN:                    | 5305-00-447-6150                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1352-06H4P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.173 Inches Minimum And 0.265 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 0.235 Inches Minimum And 0.265 Inches Maximum                       |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.218 Inches Minimum And 0.226 Inches Maximum                       |
| <b>Head Height:</b>                                   | 0.134 Inches Minimum And 0.138 Inches Maximum                       |
| <b>Hole Diameter:</b>                                 | 0.036 Inches Nominal  |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.138 Inches  |
| <b>Width Across Flats:</b>                            | 0.109 Inches Minimum And 0.111 Inches Maximum                       |
| <b>Hole Quantity:</b>                                 | 2   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 180000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>                        | 155000 Pounds Per Square Inch                                       |
| <b>Hole Configuration Style:</b>                      | Round   |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall         |
| <b>Thread Series Designator:</b>                      | Unrc  |
| <b>Specification/standard Data:</b>                   | 80205-nas1352 Professional/industrial Association Standard          |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-06H4P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.