

# P/N NAS1352-06H6P

## **Description**

length: 3/8", thread: 6-32, socket head, drilled head, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

### **Additional Information**

### **Alternate Part Numbers**

### MS24677-7

SKU / Model: NAS135206H6P

Minimum Qty (MOQ): 20

NSN: 5305-00-058-2067

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352-06H6P Specifications

	3a
Thread Direction:	Right-hand
Thread Length:	0.283 Inches Minimum
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Hole Diameter:	0.036 Inches Nominal
Internal Drive Style:	Hexagon
End Item Identification:	W/s:helicopter, Mh-53e; Aircraft, C-2a (reprocured); Engine, Aircraft, Tf39-ge-1 (c-5a); Aircraft, Osprey V-22a, Air Force; Helicopter, Carrier Based Asw, Sh-60f; Helicopter, Search And Rescue, Hh-60h; Aircraft, Osprey V-22a, Marine Corps; Aircraft, Airlifter C-17a; Engine, Aircraft, Tf-33-p-7 (c-1411a/b); Helicopter, Advance Attack, Ah-1w
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard
Nondefinitive Spec/std Data:	6 Type

# How to Order Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-06H6P">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-06H6P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.