



★ FASTENERS

Military-Fasteners.com

P/N NAS1352-06H8P

Description

Fastener Length: 33/64", Thread: 6-32, Head Width: 7/64", Thread Length: 33/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS135206H8P
Minimum Qty (MOQ):	10
NSN:	5305-00-182-9462
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1352-06H8P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.422 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	0.484 Inches Minimum And 0.516 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1352 Professional/Industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-06H8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.