

Description

Fastener Length: 17/64", Thread: 6-32, Head Width: 7/64", Thread Length: 17/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS135206LB4P
Minimum Qty (MOQ):	25
NSN:	5305-00-001-6359
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1352-06LB4P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.172 Inches Minimum And 0.266 Inches Maximum
Fastener Length:	0.234 Inches Minimum And 0.266 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Locking Feature:	Pellet Locking Feature
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Material:	Plastic Polyamide Locking Feature
Material:	Steel Uns K03104 Fastener
Material Document And Classification:	Astma574 Assn Std Single Material Response Fastener
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-06LB4P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.