

Description

length: 7/8", thread: 8-32, socket head screw - black oxide finish alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | NAS13520814 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-01-532-0994 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



P/N NAS1352-08-14 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Maximum |
| Fastener Length: | 1.034 Inches Minimum And 1.039 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.262 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.159 Inches Minimum And 0.164 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.164 Inches |
| Width Across Flats: | 0.141 Inches Minimum And 0.143 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Material: | Steel Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unrc |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-08-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.