



MILITARY ★ FASTENERS

Military-Fasteners.com

P/N NAS1352-08-28P

Description

Fastener Length: 1-3/4", Hole Diameter: 1/16", Thread: 8-32, Head Width: 9/64", Thread Length: 1-3/4", NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS13520828P
Minimum Qty (MOQ):	2
NSN:	5305-00-936-0347
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1352-08-28P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.648 Inches Minimum And 1.750 Inches Maximum
Fastener Length:	1.710 Inches Minimum And 1.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Hole Diameter:	0.064 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Hole Configuration Style:	Round Longitudinal Hole
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-08-28P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.