

Description

Fastener Length: 1-3/4", Hole Diameter: 1/16", Thread: 8-32, Head Width: 9/64", Thread Length: 1-3/4", NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS13520828P |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5305-00-936-0347 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1352-08-28P Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.648 Inches Minimum And 1.750 Inches Maximum |
| Fastener Length: | 1.710 Inches Minimum And 1.750 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.262 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.159 Inches Minimum And 0.164 Inches Maximum |
| Hole Diameter: | 0.064 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.164 Inches |
| Width Across Flats: | 0.141 Inches Minimum And 0.143 Inches Maximum |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 130000 Pounds Per Square Inch |
| Hole Configuration Style: | Round Longitudinal Hole |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-08-28P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.