

## P/N NAS1352-08-36P

## **Description**

Fastener Length: 2-1/4", Thread: 8-32, Head Width: 9/64", Thread Length: 2-1/4", NAS1352 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS13520836P

Minimum Qty (MOQ): 5

NSN: 5305-00-902-7284

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352-08-36P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.148 Inches Minimum And 2.250 Inches Maximum
Fastener Length:	2.210 Inches Minimum And 2.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.140 Inches Minimum And 0.142 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2; Class 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-08-36P">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-08-36P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.