

## P/N NAS1352-08H10P

### **Description**

Fastener Length: 5/8", Hole Diameter: 1/32", Thread: 8-32, Head Width: 9/64", Thread Length: 5/8", NAS1352 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS135208H10P

Minimum Qty (MOQ): 20

NSN: 5305-00-731-9202

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352-08H10P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Nominal
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.140 Inches Minimum And 0.142 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-08H10P">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-08H10P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.