

P/N NAS1352-08H6

Description

length: 3/8", thread: 8-32, socket head screw drilled head black oxide finish alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS135208H6

Minimum Qty (MOQ): 10

NSN: 5305-00-052-5689

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1352-08H6 Specifications

3a
Right-hand
0.375 Inches Minimum
0.375 Inches Nominal
Flat Chamfer
0.262 Inches Minimum And 0.270 Inches Maximum
0.159 Inches Minimum And 0.164 Inches Maximum
0.047 Inches Nominal
Hexagon
0.164 Inches
0.140 Inches Minimum And 0.142 Inches Maximum
6
Drilled
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
130000 Pounds Per Square Inch
Round Internal Hexagon
Steel Overall
Unc
80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-08H6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.