

## Description

Fastener Length: 7/8", Thread: 8-32, Head Width: 9/64", Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS135208LB14P
Minimum Qty (MOQ):	30 EA
NSN:	5305-01-030-2909
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1352-08LB14P Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.783 Inches Minimum And 0.875 Inches Maximum
<b>Fastener Length:</b>	0.845 Inches Minimum And 0.875 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.262 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.159 Inches Minimum And 0.164 Inches Maximum
<b>Locking Feature:</b>	Patch Threads Or Pellet Threads Or Strip Threads
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Width Across Flats:</b>	0.141 Inches Minimum And 0.143 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	155000 Pounds Per Square Inch
<b>Material:</b>	Plastic Polyamide Locking Feature
<b>Material:</b>	Steel Fastener
<b>Surface Treatment:</b>	Cadmium Fastener And Chromate Fastener
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unrc
<b>Specification/standard Data:</b>	80205-nas1352 Professional/industrial Association Standard

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-08LB14P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.