

Description

NAS1352-3-6P Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS135236P
Minimum Qty (MOQ):	25
NSN:	5305-01-139-6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N NAS1352-3-6P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.283 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/Industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-3-6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.