

Description

Length: 1.25", NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1352520P |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-01-058-5355 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1352-5-20P Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.125 Inches Nominal |
| Fastener Length: | 1.210 Inches Minimum And 1.250 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.457 Inches Minimum And 0.469 Inches Maximum |
| Head Height: | 0.306 Inches Minimum And 0.312 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.312 Inches |
| Width Across Flats: | 0.250 Inches Minimum And 0.253 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 170000 Pounds Per Square Inch |
| Hardness Rating: | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 150000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/Industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-5-20P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.