

P/N NAS1352-5-28P

Description

NAS1352-5-28P Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352528P

Minimum Qty (MOQ): 50

NSN: 5305-01-251-8155

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1352-5-28P Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 1.125 Inches Minimum |
| Fastener Length: | 1.710 Inches Minimum And 1.750 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.457 Inches Minimum And 0.469 Inches Maximum |
| Head Height: | 0.306 Inches Minimum And 0.312 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.312 Inches |
| Width Across Flats: | 0.250 Inches Minimum And 0.253 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 170000 Pounds Per Square Inch |
| Hardness Rating: | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 150000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352-5-28P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.