

P/N NAS1352C01-3

Description

Fastener Length: 13/64", Thread: 1-64, Head Width: 1/16", Thread Length: 13/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352C013

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-125-5704

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1352C01-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.141 Inches Minimum And 0.204 Inches Maximum
Fastener Length:	0.172 Inches Minimum And 0.204 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.112 Inches Minimum And 0.118 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.073 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.073 Inches
Width Across Flats:	0.062 Inches Minimum And 0.063 Inches Maximum
Thread Quantity Per Inch:	64
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C01-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.