

Description

NAS1352C02-18 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1352C0218
Minimum Qty (MOQ):	10
NSN:	5305-01-379-8656
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1352C02-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Minimum
Fastener Length:	1.125 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.112 Inches Minimum And 0.118 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.073 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.073 Inches
Width Across Flats:	0.0625 Inches Minimum And 0.0635 Inches Maximum
Thread Quantity Per Inch:	64
Material:	Steel Comp Xm-7 Overall Or Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall
Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/Industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C02-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.