

## P/N NAS1352C04-14

## **Description**

Fastener Length: 7/8", Thread: 4-40, Head Width: 3/32", Thread Length: 3/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1352C0414

Minimum Qty (MOQ): 25

NSN: 5305-01-021-9151

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 013680, Alum Screws



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352C04-14 Specifications

Thread Class:         3a           Thread Direction:         Right-hand           Thread Length:         0.750 Inches Minimum           Fastener Length:         0.845 Inches Minimum And 0.875 Inches Maximum           Head Style:         Flat Chamfer           Head Dlameter:         0.176 Inches Minimum And 0.183 Inches Maximum           Head Height:         0.108 Inches Minimum And 0.112 Inches Maximum           Head Height:         0.108 Inches Minimum And 0.112 Inches Maximum           Nominal Thread Diameter:         0.112 Inches           Width Across Flats:         0.993 Inches Minimum And 0.095 Inches Maximum           Thread Quantity Per Inch:         40           Minimum Tensile Strength:         80000 Pounds Per Square Inch           Hardness Rating:         80.00 Rockwell B Minimum Overall           Minimum Yield Strength:         30000 Pounds Per Square Inch           Material:         Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall           Material Document And Classification:         66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 3th Material Response Overall Or 65 Fed Std 5th Material Response Overall Or 65 Fed Std 5th Material Response Overall Or 65 Fed Std 5th Material Res		
Thread Length:         0.750 Inches Minimum           Fastener Length:         0.845 Inches Minimum And 0.875 Inches Maximum           Head Style:         Flat Chamfer           Head Diameter:         0.176 Inches Minimum And 0.183 Inches Maximum           Head Height:         0.108 Inches Minimum And 0.112 Inches Maximum           Internal Drive Style:         Hexagon           Nominal Thread Diameter:         0.112 Inches           Width Across Flats:         0.093 Inches Minimum And 0.095 Inches Maximum           Thread Quantity Per Inch:         40           Minimum Tensile Strength:         80.00 Pounds Per Square Inch           Hardness Rating:         80.0 Rockwell B Minimum Overall           Material:         30000 Pounds Per Square Inch           Material:         Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall           Material Document And Classification:         66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 65 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 65 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or A	Thread Class:	3a
Fastener Length: 0.845 Inches Minimum And 0.875 Inches Maximum  Head Style: Flat Chamfer  Head Diameter: 0.176 Inches Minimum And 0.183 Inches Maximum  Head Height: 0.108 Inches Minimum And 0.112 Inches Maximum  Internal Drive Style: Hexagon  Nominal Thread Diameter: 0.112 Inches  Width Across Flats: 0.093 Inches Minimum And 0.095 Inches Maximum  Thread Quantity Per Inch: 40  Minimum Tensile Strength: 80000 Pounds Per Square Inch  Hardness Rating: 80.0 Rockwell B Minimum Overall  Minimum Yield Strength: 30000 Pounds Per Square Inch  Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 384 Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 2rd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overal	Thread Direction:	Right-hand
Head Style: Flat Chamfer  Head Diameter: 0.176 Inches Minimum And 0.183 Inches Maximum  Head Height: 0.108 Inches Minimum And 0.112 Inches Maximum  Internal Drive Style: Hexagon  Nominal Thread Diameter: 0.112 Inches  Width Across Flats: 0.093 Inches Minimum And 0.095 Inches Maximum  Thread Quantity Per Inch: 40  Minimum Tensile Strength: 80000 Pounds Per Square Inch  Hardness Rating: 80.0 Rockwell B Minimum Overall  Minimum Yield Strength: 30000 Pounds Per Square Inch  Material: 30000 Pounds Per Square Inch  Material: 5teel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall  Material Document And Classification: Passivate Overall  Surface Treatment: Passivate Overall  Surface Treatment Document And Classification: Passivate Overall  Surface Treatment Document And Classification: Passivate Overall  Oq-p-35 Fed Spec Single Treatment Response Overall  Oncompany Open Open Open Open Open Open Open Open	Thread Length:	0.750 Inches Minimum
Head Diameter: 0.176 Inches Minimum And 0.183 Inches Maximum  Head Height: 0.108 Inches Minimum And 0.112 Inches Maximum  Internal Drive Style: Hexagon  Nominal Thread Diameter: 0.112 Inches  Width Across Flats: 0.093 Inches Minimum And 0.095 Inches Maximum  Thread Quantity Per Inch: 40  Minimum Tensile Strength: 800.0 Pounds Per Square Inch  Hardness Rating: 80.0 Rockwell B Minimum Overall  Minimum Yield Strength: 30000 Pounds Per Square Inch  Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall  Material Document And Classification: Passivate Overall  Surface Treatment: Passivate Overall  Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall  Thread Series Designator: Unrc	Fastener Length:	0.845 Inches Minimum And 0.875 Inches Maximum
Head Height: 0.108 Inches Minimum And 0.112 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.093 Inches Minimum And 0.095 Inches Maximum Thread Quantity Per Inch: 40 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall Material Document And Classification: Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Surface Treatment Document And Classification: Unrc	Head Style:	Flat Chamfer
Internal Drive Style:HexagonNominal Thread Diameter:0.112 InchesWidth Across Flats:0.093 Inches Minimum And 0.095 Inches MaximumThread Quantity Per Inch:40Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel OverallMaterial Document And Classification:6F Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrc	Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Nominal Thread Diameter:  Width Across Flats:  0.093 Inches Minimum And 0.095 Inches Maximum  Thread Quantity Per Inch:  40  Minimum Tensile Strength:  80000 Pounds Per Square Inch  Hardness Rating:  80.0 Rockwell B Minimum Overall  Minimum Yield Strength:  30000 Pounds Per Square Inch  Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall  Material:  66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Classification:  Surface Treatment Document And Classification:  Thread Series Designator:  Unrc	Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Width Across Flats: 0.093 Inches Minimum And 0.095 Inches Maximum  Thread Quantity Per Inch: 40  Minimum Tensile Strength: 80000 Pounds Per Square Inch  Hardness Rating: 80.0 Rockwell B Minimum Overall  Minimum Yield Strength: 30000 Pounds Per Square Inch  Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall  Material Document And Classification: Passivate Overall  Surface Treatment: Passivate Overall  Surface Treatment Document And Classification: Unrc  Thread Series Designator: Unrc	Internal Drive Style:	Hexagon
Thread Quantity Per Inch:40Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel OverallMaterial Document And Classification:66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overal	Nominal Thread Diameter:	0.112 Inches
Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 300000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall  Material Document And Classification: 66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66	Width Across Flats:	0.093 Inches Minimum And 0.095 Inches Maximum
Hardness Rating: 80.0 Rockwell B Minimum Overall  Minimum Yield Strength: 30000 Pounds Per Square Inch  Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall  Material Document And Classification: 66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Surface Treatment Document And Classification: Passivate Overall  Thread Series Designator: Unro	Thread Quantity Per Inch:	40
Minimum Yield Strength:  Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Surface Treatment Document And Classification:  Thread Series Designator:  Unrc	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material:  Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall Or 66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overa	Hardness Rating:	80.0 Rockwell B Minimum Overall
Material:  Material Document And Classification:  Surface Treatment:  Surface Treatment Document And Classification:  Thread Series Designator:  Steel Overall  Steel Overall  66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or Astm A493 Type Xm-7 A	Minimum Yield Strength:	30000 Pounds Per Square Inch
Classification:  Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall Or Astm A493 Type Xm-7 As	Material:	
Surface Treatment Document And Classification:  Thread Series Designator:  Unrc		Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material
Classification:  Classification:  Classification:  Classification:  Classification:  Unrc	Surface Treatment:	Passivate Overall
		Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1352 Professional/industrial Association Standard	Thread Series Designator:	Unrc
	Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C04-14">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C04-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C04-14">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C04-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C04-14">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C04-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/nastary-fa