

Description

Fastener Length: 49/64", Hole Diameter: 1/32", Thread: 4-40, Head Width: 3/32", Thread Length: 47/64", drilled, NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352C04H12
Minimum Qty (MOQ):	10
NSN:	5305-00-983-9469
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1352C04H12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.684 Inches Minimum And 0.734 Inches Maximum
Fastener Length:	0.734 Inches Minimum And 0.766 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Hole Diameter:	0.037 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.093 Inches Minimum And 0.095 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Comp 3130 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C04H12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.