

Description

Fastener Length: 1/4", Thread: 4-40, Head Width: 3/32", Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352C04LN4
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-924-8221
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1352C04LN4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.200 Inches Minimum
Fastener Length:	0.250 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.0937 Inches Minimum And 0.0952 Inches Maximum
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Nominal Overall
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C04LN4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.