

# P/N NAS1352C06-20

Military-Fasteners.com

#### Description

length: 1-1/4", thread: 6-32, socket head screw, corrosion resistant steel, passivated

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1352C0620
Minimum Qty (MOQ):	25
NSN:	5305-00-033-7683
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1352C06-20 Specifications

Interact Class.3aThread Direction:Right-handThread Length:0.750 Inches Minimum And 1.250 Inches MaximumFastener Length:1.210 Inches Minimum And 0.226 Inches MaximumHead Style:Flat ChamferHead Diameter:0.218 Inches Minimum And 0.226 Inches MaximumHead Height:0.134 Inches Minimum And 0.138 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.138 InchesWidth Across Flats:0.109 Inches Minimum And 0.111 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.00 Rockwell B Minimum OverallMinimum Yleld Strength:6000 Pounds Per Square InchMaterial:0000 Pounds Per Square InchMaterial:80000 Pounds Per Square InchMaterial:66 Fed Std All Material Responses Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overal	Thread Class:	3a
Thread Length:0.750 Inches Minimum And 1.250 Inches MaximumFastener Length:1.210 Inches Minimum And 1.250 Inches MaximumHead Style:Flat ChamferHead Diameter:0.218 Inches Minimum And 0.226 Inches MaximumHead Height:0.134 Inches Minimum And 0.138 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.139 Inches Minimum And 0.118 Inches MaximumOntorial Thread Diameter:0.109 Inches Minimum And 0.111 Inches MaximumWidth Across Flats:0.109 Inches Minimum And 0.111 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:8000 Pounds Per Square InchMaterial:0.000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 O		
Fastener Length:1.210 Inches Minimum And 1.250 Inches MaximumHead Style:Flat ChamferHead Diameter:0.218 Inches Minimum And 0.226 Inches MaximumHead Height:0.134 Inches Minimum And 0.138 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.138 InchesWidth Across Flats:0.109 Inches Minimum And 0.111 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:0.000 Pounds Per Square InchMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 O	Thread Direction:	Right-hand
Head Style:Flat ChamferHead Diameter:0.218 Inches Minimum And 0.226 Inches MaximumHead Height:0.134 Inches Minimum And 0.138 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.138 Inches0.138 Inches0.109 Inches Minimum And 0.111 Inches MaximumWidth Across Flats:0.109 Inches Minimum And 0.111 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:8000 Pounds Per Square InchHardness Rating:80.00 Pounds Per Square InchMinimum Yield Strength:3000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall	Thread Length:	0.750 Inches Minimum
Head Diameter:0.218 Inches Minimum And 0.226 Inches MaximumHead Height:0.134 Inches Minimum And 0.138 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.138 InchesWidth Across Flats:0.109 Inches Minimum And 0.111 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.00 Rockwell B Minimum OverallMinimum Yield Strength:9000 Pounds Per Square InchMaterial:Sele Comp 302 Overall Or Stele Comp 303 Overall Or Stele Comp 304 Overall Or Stele Comp 305 Overall Or Stele Comp 304 Overall Or Stele Comp 305 Overall	Fastener Length:	1.210 Inches Minimum And 1.250 Inches Maximum
Head Height:0.134 Inches Minimu And 0.138 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.138 InchesWidth Across Flats:0.109 Inches Minimum And 0.111 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:8000 Pounds Per Square InchHardness Rating:80.00 Rockwell B Minimum OverallMinimum Yield Strength:8000 Pounds Per Square InchMaterial:Stel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel	Head Style:	Flat Chamfer
Internal Drive Style:HexagonNominal Thread Diameter:0.138 InchesWidth Across Flats:0.109 Inches Minimum And 0.111 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.00 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Co	Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Nominal Thread Diameter:0.138 InchesWidth Across Flats:0.109 Inches Minimum And 0.111 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.000 Pounds Per Square InchMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305	Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Width Across Flats:0.109 Inches Minimum And 0.111 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 OverallMaterial Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:passivate OverallSurface Treatment Document And Classification:q-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrc	Internal Drive Style:	Hexagon
Thread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp	Nominal Thread Diameter:	0.138 Inches
Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 3	Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Hardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:3000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Overall Overall Overall Overall Overall Overall Overall Overall Overal	Thread Quantity Per Inch:	32
Minimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 305Material Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:0q-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrc	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 OverallMaterial Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment Document And Classification:9assivate OverallSurface Treatment Document And Classification:0q-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrc	Hardness Rating:	80.0 Rockwell B Minimum Overall
Material:OverallMaterial Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Oq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrc	Minimum Yield Strength:	30000 Pounds Per Square Inch
Surface Treatment: Passivate Overall   Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall   Thread Series Designator: Unrc	Material:	
Surface Treatment Document And   Qq-p-35 Fed Spec Single Treatment Response Overall     Classification:   Unrc	Material Document And Classification:	66 Fed Std All Material Responses Overall
Classification: Qq-p-35 Fed Spec Single Treatment Response Overall   Thread Series Designator: Unrc	Surface Treatment:	Passivate Overall
-		Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1352 Professional/industrial Association Standard	Thread Series Designator:	Unrc
	Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

### How to Order

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C06-20</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.