



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS1352C06H14**

## Description

Fastener Length: 57/64", Hole Diameter: 1/32", Thread: 6-32, Head Width: 7/64", Thread Length: 3/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1352C06H14                             |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5305-00-026-1996                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

# P/N NAS1352C06H14 Specifications

|  |  |
|--|--|
| Thread Class:                                  | 3a   |
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.750 Inches Minimum   |
| Fastener Length:                               | 0.859 Inches Minimum And 0.891 Inches Maximum  |
| Head Style:                                    | Flat Chamfer   |
| Head Diameter:                                 | 0.218 Inches Minimum And 0.226 Inches Maximum  |
| Head Height:                                   | 0.134 Inches Minimum And 0.138 Inches Maximum  |
| Hole Diameter:                                 | 0.036 Inches Nominal   |
| Internal Drive Style:                          | Hexagon  |
| Nominal Thread Diameter:                       | 0.138 Inches   |
| Width Across Flats:                            | 0.109 Inches Minimum And 0.111 Inches Maximum  |
| Hole Quantity:                                 | 2  |
| Hole Type:                                     | Drilled  |
| Thread Quantity Per Inch:                      | 32   |
| Minimum Tensile Strength:                      | 80000 Pounds Per Square Inch   |
| Hardness Rating:                               | 80.0 Rockwell B Minimum Overall  |
| Minimum Yield Strength:                        | 30000 Pounds Per Square Inch   |
| Hole Configuration Style:                      | Round Internal Hexagon   |
| Material:                                      | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall  |
| Material Document And Classification:          | 66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm-a493 Aisi Xm-7 Assn Std 6th Material Response Overall |
| Surface Treatment:                             | Passivate Overall  |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| Thread Series Designator:                      | Unc  |
| Specification/standard Data:                   | 80205-nas1352 Professional/industrial Association Standard   |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C06H14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.