

Description


length: 3/8", thread: 6-32, socket head, drilled head, corrosion resistant steel, passivated, NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1352C06H6 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-00-145-0940 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1352C06H6 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.297 Inches Minimum And 0.391 Inches Maximum |
| Fastener Length: | 0.359 Inches Minimum And 0.391 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.218 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.134 Inches Minimum And 0.138 Inches Maximum |
| Hole Diameter: | 0.036 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.138 Inches |
| Width Across Flats: | 0.109 Inches Minimum And 0.111 Inches Maximum |
| Hole Quantity: | 2 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Hole Configuration Style: | Round |
| Material: | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C06H6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.