

**Description**

Fastener Length: 1/2", Thread: 6-32, Head Width: 1/8", Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1352C06LL8
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-050-4219
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1352C06LL8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Fastener Length:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.218 Inches Minimum And 0.226 Inches Maximum
<b>Head Height:</b>	0.134 Inches Minimum And 0.138 Inches Maximum
<b>Locking Feature:</b>	Patch Threads Or Pellet Threads Or Strip Threads
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Width Across Flats:</b>	0.133 Inches Minimum And 0.138 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Yield Strength:</b>	30000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C06LL8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.