

Description

Fastener Length: 1/2", Thread: 6-32, Head Width: 1/8", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1352C06LL8 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5305-00-050-4219 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1352C06LL8 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Fastener Length: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.218 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.134 Inches Minimum And 0.138 Inches Maximum |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.138 Inches |
| Width Across Flats: | 0.133 Inches Minimum And 0.138 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unc |

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C06LL8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.