

**Description**

length: 3/4, thread: 8-32, socket head screw, corrosion resistant steel, passivated, NAS1352 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS16995-28](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1352C0812  |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5305-00-403-3497                                    |
| Schedule B:             | 7318.15.2091  |
| ECCN:                   | 9A991   |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |



## P/N NAS1352C08-12 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                               | 3a   |
| <b>Thread Direction:</b>                           | Right-hand   |
| <b>Thread Length:</b>                              | 0.688 Inches Minimum And 0.750 Inches Maximum  |
| <b>Fastener Length:</b>                            | 0.720 Inches Minimum And 0.750 Inches Maximum  |
| <b>Head Style:</b>                                 | Flat Chamfer   |
| <b>Head Diameter:</b>                              | 0.262 Inches Minimum And 0.270 Inches Maximum  |
| <b>Head Height:</b>                                | 0.159 Inches Minimum And 0.164 Inches Maximum  |
| <b>Width Between Flats:</b>                        | 0.141 Inches Minimum And 0.143 Inches Maximum  |
| <b>Internal Drive Style:</b>                       | Err-090  |
| <b>Nominal Thread Diameter:</b>                    | 0.164 Inches   |
| <b>Width Across Flats:</b>                         | 0.141 Inches Minimum And 0.143 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                   | 32   |
| <b>Minimum Tensile Strength:</b>                   | 80000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                            | 80.0 Rockwell B Minimum  |
| <b>Screw Material:</b>                             | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 |
| <b>Screw Material Document And Classification:</b> | Astm A493 Assn Std All Material Responses  |
| <b>Screw Surface Treatment:</b>                    | Passivate  |
| <b>Thread Series Designator:</b>                   | Unrc   |
| <b>Specification/standard Data:</b>                | 80205-nas1352 Professional/Industrial Association Standard   |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.