



★ FASTENERS

Military-Fasteners.com

P/N NAS1352C08-12

Description

length: 3/4, thread: 8-32, socket head screw, corrosion resistant steel, passivated, NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS16995-28](#)

SKU / Model:	NAS1352C0812
Minimum Qty (MOQ):	25
NSN:	5305-00-403-3497
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N NAS1352C08-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Width Between Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Internal Drive Style:	Err-090
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384
Screw Material Document And Classification:	Astm A493 Assn Std All Material Responses
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.