

## P/N NAS1352C08-20

### **Description**

Fastener Length: 1-7/32", Thread: 8-32, Head Width: 3/32", Thread Length: 7/8", NAS1352 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

#### NAS1352C0820

SKU / Model: NAS1352C0820

Minimum Qty (MOQ): 25

NSN: 5305-00-116-1539

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352C08-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Nominal
Fastener Length:	1.234 Inches Nominal
Head Style:	Dee Chamfer
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.109 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Nominal Overall
Part Name Assigned By Controlling Agency:	Screw, Cap, Socket Head, Drilled
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Federal Standard All Material Responses Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Federal Spec Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205 - Nas 1352 National Std/spec

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08-20">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08-20</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.