

Description

Fastener Length: 1-7/32", Thread: 8-32, Head Width: 3/32", Thread Length: 7/8", NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[NAS1352C0820](#)

SKU / Model:	NAS1352C0820
Minimum Qty (MOQ):	25
NSN:	5305-00-116-1539
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1352C08-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Nominal
Fastener Length:	1.234 Inches Nominal
Head Style:	Dee Chamfer
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.109 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Nominal Overall
Part Name Assigned By Controlling Agency:	Screw, Cap, Socket Head, Drilled
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Federal Standard All Material Responses Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Federal Spec Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205 - Nas 1352 National Std/spec

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.