

P/N NAS1352C08-5

Description

Fastener Length: 5/16", Thread: 8-32, Head Width: 9/64", Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352C085

Minimum Qty (MOQ): 50

NSN: 5305-01-186-5379

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1352C08-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.247 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.309 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.1406 Inches Minimum And 0.1426 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell C Minimum Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.