



Military-Fasteners.com

P/N NAS1352C08-7P

Description

Fastener Length: 7/16", Thread: 8-32, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352C087P
Minimum Qty (MOQ):	5
NSN:	5305-01-371-1771
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1352C08-7P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Maximum
Fastener Length:	0.408 Inches Minimum And 0.438 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Width Between Flats:	0.1406 Inches Minimum And 0.1426 Inches Maximum
Internal Drive Style:	Err-090
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.1406 Inches Minimum And 0.1426 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum And 42.0 Rockwell C Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or Steel Comp Xm-7
Screw Material Document And Classification:	Astm A493 Assn Std All Material Responses
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08-7P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.