

P/N NAS1352C08H16

Military-Fasteners.com

Description

Fastener Length: 63/64", Hole Diameter: 3/64", Thread: 8-32, Head Width: 9/64", Thread Length: 7/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1352C08H16
Minimum Qty (MOQ):	10
NSN:	5305-01-173-7827
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1352C08H16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum
Fastener Length:	0.970 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Hole Diameter:	0.044 Inches Minimum And 0.050 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08H16</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.