

Description

NAS1352C08H8 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352C08H8
Minimum Qty (MOQ):	20
NSN:	5305-00-988-5308
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1352C08H8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.579 Inches Minimum
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.195 Inches Maximum
Hole Diameter:	0.050 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08H8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.