

**Description**

Fastener Length: 5/8", Hole Diameter: 3/64", Thread: 8-32, Head Width: 9/64", Thread Length: 17/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1352C08H8P
Minimum Qty (MOQ):	5
NSN:	5305-01-524-6818
Schedule B:	7318.15.2091
ECCN:	EAR99



## P/N NAS1352C08H8P Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.533 Inches Minimum
<b>Fastener Length:</b>	0.595 Inches Minimum And 0.625 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.262 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.159 Inches Minimum And 0.164 Inches Maximum
<b>Hole Diameter:</b>	0.044 Inches Minimum And 0.050 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Width Across Flats:</b>	0.1406 Inches Minimum And 0.1426 Inches Maximum
<b>Hole Quantity:</b>	6
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	100000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 302 Overall
<b>Thread Series Designator:</b>	Unrc

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08H8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.