



Military-Fasteners.com

P/N NAS1352C08LB6P

Description

Fastener Length: 3/8", Hole Diameter: 3/64", Thread: 8-32, Head Width: 9/64", Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352C08LB6P
Minimum Qty (MOQ):	10
NSN:	5305-01-445-3802
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1352C08LB6P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Nominal
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Fillister
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.148 Inches Nominal
Hole Diameter:	0.044 Inches Minimum And 0.050 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.1640 Inches
Width Across Flats:	0.141 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Overall
Material Document And Classification:	Ff-s-86,cres Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unrc

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08LB6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.