

P/N NAS1352C08LE10

Description

Fastener Length: 5/8", Thread: 8-32, Head Width: 9/64", Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352C08LE10

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-386-0989

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1352C08LE10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.1406 Inches Minimum And 0.1426 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08LE10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08LE10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08LE10 and selecting the quantity you want then click "add to cart".