

**Description**

Fastener Length: 3/4", Thread: 1/2-13, Head Width: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1352C08LL5
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-416-5236
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N NAS1352C08LL5 Specifications

<b>Thread Class:</b>	3a
<b>Fastener Length:</b>	0.720 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.735 Inches Minimum And 0.750 Inches Maximum
<b>Head Height:</b>	0.492 Inches Minimum And 0.500 Inches Maximum
<b>Locking Feature:</b>	Strip Locking Feature
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Width Across Flats:</b>	0.3750 Inches Minimum And 0.3790 Inches Maximum
<b>Thread Quantity Per Inch:</b>	13
<b>Material:</b>	Plastic Polyamide Locking Feature
<b>Material:</b>	Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener Or Steel Comp Xm-7 Fastener
<b>Material Document And Classification:</b>	Astm A493 Assn Std All Material Responses Fastener
<b>Thread Series Designator:</b>	Unrc

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08LL5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.